

Quick installation eZy Box Elocky



To install the eZy box, the supplied power supply must first be plugged into the mains and connected to the box via the micro USB port. Then wait about **1 minute** until both LEDs in the box flash. (Green and orange LEDs on top).

The green LED (left) represents the Bluetooth communication status of the Box.

The orange LED (right) represents the status of the Box's Internet communication. Once both LEDs blink, bring the Elocky mobile application:

How to install a beacon?

- Open the battery cover to remove the protective plastic (below the battery)
- Close the beacon
- Go to the objects menu, then add the beacon by giving it a name.

1 Go to the «**Objects**» menu

2 Click the **(+)** button at the top right of the screen

3 Select **(ELOCKY BOX)**

4 Wait until **the Box appears on the pop-up** and select it: ☒

5 **Give it a name** (example: box input) then validate

6 Select **Ethernet or wifi** for the web connection

7 If you have selected **Ethernet**, **connect the eZy box to your internet box with an RJ45 cable** (not supplied) and validate.

8 If you have selected **wifi**, **enter the name of the wifi of your internet box, as well as its password** (respecting uppercase and lowercase) then validate.

9 Finally, wait until both **LEDs are lit and steady**. Once your eZy box is well added, it should appear on the mobile application in **the objects page on the Elocky Box tab**. Now all you have to do is link your box to the Elocky Bluetooth objects you want it to control :

10 Click **on the button (links)** and select **the object to link** : lock, or beacon Your eZy box is now operational. Alarm setting and remote activation.

11 You can use a paper clip tip to press the button to the right of the LEDs:

- **1 short press** : **restarts the eZy box softwares**, retains the configuration.
- **4 short and successive pressings** : **turns off the box** without disconnecting the power supply.
- **2 short and successive pressings** : **restart the Web connection** (Wifi or wired)
- **5 short and successive pressings** : **clear the Web access configuration (reset box)**