


Installation Instructions




Keep emergency keys outdoors in a safe place.


1 Remove the cap from the inner handle, by pressing the black circles :



2 Mount the battery, holding the battery holder firmly :



3 Reassemble the cap, remaining aligned on the axis :



Hold the cylinder horizontally, blocking the **lock bit**, and turn the outer knob to move the outer knob clamping **screw upwards**.



When reassembling press on its black semi-circles, then push in while remaining aligned, until the CLIC. Holding the cylinder horizontally by the bit, the outer knob must rotate freely.




Installation Instructions



Keep emergency keys outdoors in a safe place.

4


Remove the outer knob and slide eVy into the lock :



Unscrew **screw 1** if necessary with the Allen key.
Gently pull in the axis
Then remove the original cylinder
And put eVy back on the target lock.
Screw 2, fixed on the axis, **downwards**
Do not attempt to tighten screw 2


When reassembling, the eVy cylinder must slide without obstruction.
If necessary, loosen the lock and its fittings to give the assembly some room for play

Cylinder clamping screw : **reuse the original one or use the one supplied with eVy**



5

Gently reassemble the outer button :



Gently reassemble the external button
Make sure to position the knob with **screw 2** facing the notch, so the internal connector in the knob will be facing the axial female connector.

Once the connector is engaged, press down the knob at the stop and then retighten **screw 1** with the Allen wrench, **without forcing**.

